## Give your pasture that well-groomed look!







The 1" thick, 4" wide reinforcement aids the dishpan in withstanding the constant punishment the overall drivetrain must endure.



The heavy-duty turnbuckle keeps the center and wing axles at the same cutting height. With grease fittings incorporated in the turnbuckle, free motion is maintained for quality performance.



· Smooth top for easy clean off

	RC3615 MEDIUM DUTY
Horsepower	50-160 HP
Hitch	Pull-Type; Standard Clevis, LP Performance Self-Leveling, Pintle, Ball, Bar-Tite
Working Width (cm)	15' (457)
Overall Width	15' 8"
Min. Transport Width	8'
Overall Length	15' 6"
Machine Weight - Ib (kg)	3,730 (1692)
Tongue Weight - Ib	1,240
Cutting Height	2" - 14"
Cutting Capacity	2-1/2"
Height Adjustment	3" x 8" Cylinder, Hose, Fittings & Stroke Control Spacers
Deck Thickness	10 Gauge
Deck Height	12"
Deck Shock Protection	Spring Cushioned Center Axle
Deck Rings	Optional
Side Thickness	1/4"
Safety Guards (must choose)	Front & Rear: Single or Double Chain or Rubber
Skid Shoes	Wings and Center, Replaceable
Blades (2 per section)	1/2" x 4" Heat Treated Free Swinging Alloy Steel w/Uplift
Blade Bolt	Keyed with Hardened Flatwasher & Lock Nut
Blade Overlap	6"
Blade Tip Speed (Feet per minute)	540 RPM: 15,268 fpm on Center, 15,000 fpm on Wings 1000 RPM: 15,578 fpm on Center, 14,620 fpm on Wings
Dishpan	3/16" Round, Dish Shaped with 1" x 4" Blade Bar
Hydraulics	Wings: 2-1/2" x 12" Cylinder, Hoses & Fittings
Gearbox Rating^	540 or 1000 RPM: 160 HP Divider, 130 HP Center & Wings
Gearbox Output Shaft	2"
Gearbox Input Shaft	1-3/4" 20 Spline
Input Driveline	Cat. 6 CV
Connecting Drivelines	Cat. 4 with Slip-Clutch
Max. Turning Angle	80° w/Constant Velocity U-Joint
Tires - 4 or 6	21" Laminated 29" Used Aircraft 25.5" Foam-Filled

<sup>\*</sup>See dealer for complete warranty information.

Color Options:





superior support from section to section

<sup>^</sup>Based on field performance.